Refine Search

Search Results -

Terms	Documents
L2 same hot	37

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L4

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: Friday, July 01, 2005   Printable Copy   Create Case

Set Name	Query	Hit Count	Set Name
side by side			result set
	DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L4	L2 same hot	37	L4
L3	L2 same "hot-plug"	2	L3
L2	sens$3 near5 (insert$3 or remov$3) near10 signal	5598	L2
L1	sens$3 same (insert$3 or remov$3) same signal	69809	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
L4	0

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L5

Refine Search

Recall Text ⬍   Clear   Interrupt

Search History

DATE: Friday, July 01, 2005   Printable Copy   Create Case

Set Name Query	Hit Count	Set Name
side by side		result set
DB=EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR		
L5 L4	0	L5
DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L4 L2 same hot	37	L4
L3 L2 same "hot-plug"	2	L3
L2 sens$3 near5 (insert$3 or remov$3) near10 signal	5598	L2
L1 sens$3 same (insert$3 or remov$3) same signal	69809	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
4941841.pn. or 5010426.pn. or 5045960.pn. or 5717571.pn. or 5721669.pn. or 6266724.pn. or 6131134.pn.	7

Database:

US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L1

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: Friday, July 01, 2005   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
	DB=USPT; PLUR=YES; OP=OR		
L1	4941841.pn. or 5010426.pn. or 5045960.pn. or 5717571.pn. or 5721669.pn. or 6266724.pn. or 6131134.pn.	7	L1

END OF SEARCH HISTORY

Freeform Search

Database:

```
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins
```

Term:

```
L1 and (signal same (insert$3 or remov$3))
```

Display: `10` Documents in **Display Format:** `TI` **Starting with Number** `1`

Generate: ○ **Hit List** ◉ **Hit Count** ○ **Side by Side** ○ **Image**

[Search] [Clear] [Interrupt]

Search History

DATE: Friday, July 01, 2005   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=USPT; PLUR=YES; OP=OR			
L4	L1 and (signal same (insert$3 or remov$3))	1	L4
L3	L1 and (sens$3 same (insert$3 or remov$3))	1	L3
L2	L1 and (sens$3 near5 (insert$3 or remov$3))	0	L2
L1	4941841.pn. or 5010426.pn. or 5045960.pn. or 5717571.pn. or 5721669.pn. or 6266724.pn. or 6131134.pn.	7	L1

END OF SEARCH HISTORY

Refine Search

Search Results -

Terms	Documents
(710/301 |710/302).ccls. and ((sens$3 near5 (insert$3 or remov$3)) same signal)	26

Database:
```
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins
```

Search: L6

[Refine Search]

[Recall Text ⬍]   [Clear]   [Interrupt]

Search History

DATE: **Friday, July 01, 2005**   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=USPT; PLUR=YES; OP=OR			
L6	710/301-302.ccls. and ((sens$3 near5 (insert$3 or remov$3)) same signal)	26	L6
L5	710/301-302.ccls. and (sens$3 near5 (insert$3 or remov$3))	48	L5
L4	L1 and (signal same (insert$3 or remov$3))	1	L4
L3	L1 and (sens$3 same (insert$3 or remov$3))	1	L3
L2	L1 and (sens$3 near5 (insert$3 or remov$3))	0	L2
L1	4941841.pn. or 5010426.pn. or 5045960.pn. or 5717571.pn. or 5721669.pn. or 6266724.pn. or 6131134.pn.	7	L1

END OF SEARCH HISTORY

IEEE Xplore RELEASE 2.0

Welcome United States Patent and Trademark Office

Search Results

BROWSE   SEARCH   IEEE XPLORE GUIDE   SUPPORT

Results for "(sens* and insert* and hot and signal and control*<in>metadata) <and> (remov*<in&..."

Your search matched **10** of **1189536** documents.

A maximum of **100** results are displayed, **25** to a page, sorted by **Relevance** in **Descending** order.

e-mail printer friendly

· » View Session History

» New Search

Modify Search

» Key

(sens* and insert* and hot and signal and control*<in>metadata) <and> (remov*<in >>

IEEE JNL	IEEE Journal or Magazine
IEE JNL	IEE Journal or Magazine
IEEE CNF	IEEE Conference Proceeding
IEE CNF	IEE Conference Proceeding
IEEE STD	IEEE Standard

Check to search only within this results set

Display Format: ◉ Citation   ○ Citation & Abstract

Select   Article Information

☐ 1. **Rule-based autotuning based on frequency domain identification**
McCormack, A.S.; Godfrey, K.R.;
Control Systems Technology, IEEE Transactions on
Volume 6, Issue 1, Jan. 1998 Page(s):43 - 61

AbstractPlus | References | Full Text: PDF(420 KB)   IEEE JNL.

☐ 2. **A behavioral synthesis system for asynchronous circuits**
Sacker, M.; Brown, A.D.; Rushton, A.J.; Wilson, P.R.;
Very Large Scale Integration (VLSI) Systems, IEEE Transactions on
Volume 12, Issue 9, Sept. 2004 Page(s):978 - 994

AbstractPlus | References | Full Text: PDF(872 KB)   IEEE JNL.

☐ 3. **Distributing the Frontend for Temperature Reduction**
Chaparro, P.; Magklis, G.; Gonzalez, J.; Gonzalez, A.;
High-Performance Computer Architecture, 2005. HPCA-11. 11th International Symposium on
12-16 Feb. 2005 Page(s):61 - 70

AbstractPlus | Full Text: PDF(344 KB)   IEEE CNF

☐ 4. **An algorithm for curve and surface fitting using B-splines**
Kitson, F.L.;
Acoustics, Speech, and Signal Processing, 1989. ICASSP-89., 1989 International Conference on
23-26 May 1989 Page(s):1207 - 1210 vol.2

AbstractPlus | Full Text: PDF(256 KB)   IEEE CNF

☐ 5. **Asynchronous circuit synthesis by direct mapping: interfacing to environment**
Bystrov, A.; Yakovlev, A.;
Asynchronous Circuits and Systems, 2002. Proceedings. Eighth International Symposium on
8-11 April 2002 Page(s):127 - 136

AbstractPlus | Full Text: PDF(453 KB)   IEEE CNF

☐ 6. **The fabrication of all-diamond packaging panels with built-in interconnects for wireless integrated microsystems**
Xiangwei Zhu; Aslam, D.M.; Yuxing Tang; Stark, B.H.; Najafi, K.;
Microelectromechanical Systems, Journal of
Volume 13, Issue 3, June 2004 Page(s):396 - 405

AbstractPlus | References | Full Text: PDF(824 KB)   IEEE JNL.

☐ 7. **Water-cooled, high-intensity ultrasound surgical applicators with frequency tracking**
Martin, R.W.; Vaezy, S.; Proctor, A.; Myntti, T.; Lee, J.B.J.; Crum, L.A.;
Ultrasonics, Ferroelectrics and Frequency Control, IEEE Transactions on
Volume 50, Issue 10, Oct. 2003 Page(s):1305 - 1317

AbstractPlus | Full Text: PDF(918 KB) IEEE JNL

8. **Portable system for imaging of /spl alpha/, and X-ray sources with silicon pixel detectors and Medipix1 readout**
Bertolucci, E.; Boerkamp, T.; Maiorino, M.; Mettivier, G.; Montesi, M.C.; Russo, P.;
Nuclear Science, IEEE Transactions on
Volume 49, Issue 4, Aug. 2002 Page(s):1845 - 1850

AbstractPlus | References | Full Text: PDF(573 KB) IEEE JNL

9. **The MD 122 dual 3 Mbyte flexible disk drive**
Stewart, A.;
Magnetics, IEEE Transactions on
Volume 17, Issue 4, Jul 1981 Page(s):1403 - 1407

AbstractPlus | Full Text: PDF(624 KB) IEEE JNL

10. **Mechatronics-motion control for teaching and research**
Dunlop, G.R.;
Mechatronics and Machine Vision in Practice, 1997. Proceedings., Fourth Annual Conference on
23-25 Sept. 1997 Page(s):2 - 7

AbstractPlus | Full Text: PDF(700 KB) IEEE CNF

Help   Contact Us   Privacy & Security   IEEE.org

Indexed by
Inspec+

IEEE Xplore RELEASE 2.0

AbstractPlus

◄ View Search Results | ◄ Previous Article | Next Article ►

The MD 122 dual 3 Mbyte flexible disk drive

Stewart, A.
Burroughs Machines Ltd., Glenrothes, Scotland

This paper appears in: **Magnetics, IEEE Transactions on**
Publication Date: Jul 1981
Volume: 17 , Issue: 4
On page(s): 1403 - 1407
ISSN: 0018-9464
Posted online: 2003-01-06 16:52:34.0

Abstract
The dual 3Mbyte flexible disk drive provides 6 Mbyte of formatted data storage in a compact package designed for in-built use. The two disks may be **inserted** or **removed** independently and share a common double ended spindle. A common actuator is used to position the four recording heads. High areal recording density is achieved using advanced technology recording heads and media in association with a microprocesor **controlled** environmentally compensated servo positioner. The drive incorporates an intelligent **controller** which provides sophisticated data handling functions and **controls** the drive in such a manner that the interface to the host is free of drive dependant parameters.

Index Terms
Inspec

Controlled Indexing
Not Available

Author Keywords
Not Available

Non-controlled Indexing
Magnetic disk recording

References
No references available on IEEE Xplore.

Citing Documents
No citing documents available on IEEE Xplore.

Access this document

Full Text: PDF (624 KB)

Download this citation

Choose   Citation

Download EndNote, ProCite, RefMan

» Learn More

Rights & Permissions

REQUEST PERMISSIONS
RIGHTS

» Learn More

Help   Contact Us   Privacy & Security   IEEE.org

L4: Entry 17 of 37   File: USPT   Jul 10, 2001

DOCUMENT-IDENTIFIER: US 6260155 B1
TITLE: Network information server

Brief Summary Text (14):
The invention accordingly provides for an information server system having a scalable, modular,
fault tolerant, hot swappable architecture of a plurality of components for interfacing with a
computer network such as the Internet, comprising a central processing unit, a communications
interface subsystem connected to the central processing unit, a mass storage subsystem
connected to the central processing unit, and a diagnostics computer subsystem connected to the
central processing unit for monitoring when one of the plurality of components of the
information server system is removed or added. In a presently preferred embodiment, the
information server system further comprises a mid-plane connector board having a plurality of
sockets for connecting the components on each side of the mid-plane connector board, and the
components of the information server system are currently preferably connected to the mid-plane
connector board of the information server system by interface cards. In a preferred aspect of
the invention, the interface cards comprise circuitry to sense when the interface cards are
failing or are being removed, and to generate a signal to the diagnostics subsystem of the
information server system indicating that the component connected to the connector board by the
interface card is to be taken off line, to allow the information server system to switch the
components off as they are taken off-line, and to switch them on as they are placed on-line,
allowing the information system to be fully hot-swappable. Each the component preferably has a
unique electronic serial number recognized by the diagnostics subsystem, allowing the
components to be integrated into the information server system.

Brief Summary Text (16):
In one presently preferred embodiment, the mass storage subsystem comprises a plurality of disk
storage devices, and each of the plurality of disk storage devices is mounted on a bypass
interface card that connects to a mid-plane connector board having a plurality of sockets for
connecting interface cards for components on each side of the mid-plane connector board. The
bypass interface cards are sequentially connectable together by jumper cables, so that a
plurality of disk storage devices can be connected together. In a currently preferred aspect,
the bypass interface cards include circuitry to sense when a bypass interface card is failing
or is being removed, and to generate a signal to the diagnostics subsystem of the information
server system indicating that the disk storage device connected to the connector board by the
bypass interface card is to be taken off line, to allow the information server system to switch
the disk storage components off as they are taken off-line, and to switch them on as they are
placed on-line, allowing the information system to be fully hot-swappable. In one presently
preferred embodiment, the mass storage subsystem comprises a fibre channel disk storage device
array subsystem.

Detailed Description Text (6):
Each mid-plane connector board advantageously has sockets 28 for connecting interface cards for
components on each side of the mid-plane connector board, and each mid-plane connector board
further can have upper and lower sets of sockets, allowing for components to be mirrored left
and right, and top and bottom, to significantly increase fault tolerance of the information
server system. Multiple mid-plane connector boards can be utilized in the information server
system, allowing for expansion and scalability of the system. Each of the bypass interface
cards are sequentially connectable together by jumper cables, so that any number of disk
storage. devices can be connected together to make the configuration scalable to up to any
needed mass storage configuration, limited only by the size of space available for disk storage
provided by the physical server case framework. As is further explained in greater detail
below, the diagnostics subsystem monitors the serial numbers for the components on-line, and
monitors when a component is removed or added. Each bypass interface card preferably includes

circuitry to <u>sense when a bypass interface card is failing or is being removed, and to generate</u> <u>a signal</u> to the diagnostics subsystem of the information server system indicating that the individual is to be taken off line, to allow the information server system to switch the disk storage components off as they are taken off-line, and to switch them on as they are placed on-line, allowing the information system to be fully <u>hot</u>-swappable.

CLAIMS:

3. The information server system of claim 2, wherein said interface cards comprise circuitry to <u>sense when the interface cards are failing or is being removed, and to generate a signal</u> to the diagnostics subsystem of the information server system indicating that the component connected to the connector board by the interface card is to be taken off line, to allow the information server system to switch the components off as they are taken off-line, and to switch them on as they are placed on-line, allowing the information system to be fully <u>hot</u>-swappable.

11. The information server system of claim 10, wherein each of said bypass interface cards include circuitry to <u>sense when a bypass interface card is failing or is being removed, and to</u> <u>generate a signal</u> to the diagnostics subsystem of the information server system indicating that the disk storage device connected to the connector board by the bypass interface card is to be taken off line, to allow the information server system to switch the disk storage components off as they are taken off-line, and to switch them on as they are placed on-line, allowing the information system to be fully <u>hot</u>-swappable.

<u>Previous Doc</u>   <u>Next Doc</u>   <u>Go to Doc#</u>

☐ ▒▒ Generate Collection ▒▒ | Print |

L4: Entry 17 of 37   File: USPT   Jul 10, 2001

US-PAT-NO: 6260155
DOCUMENT-IDENTIFIER: US 6260155 B1

TITLE: Network information server

DATE-ISSUED: July 10, 2001

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Dellacona; Richard	Riverside	CA		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
QUAD Research	Riverside	CA			02

APPL-NO: 09/ 071282   [PALM]
DATE FILED: May 1, 1998

INT-CL: [07] G06 F 11/00

US-CL-ISSUED: 714/4; 714/46
US-CL-CURRENT: 714/4; 714/46

FIELD-OF-SEARCH: 714/2, 714/4, 714/6, 714/7, 714/8, 714/13, 714/14, 714/25, 714/30, 714/39, 714/46, 714/47, 370/220, 370/226, 709/238, 709/239, 709/242, 710/102, 710/103, 380/255, 702/130, 702/142, 702/146, 375/354

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

▒▒ Search Selected ▒▒ | ▒▒ Search ALL ▒▒ | ▒▒ Clear ▒▒

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4347563	August 1982	Paredes et al.	
☐	4590554	May 1986	Glazer et al.	
☐	4710926	December 1987	Brown et al.	
☐	4773313	September 1988	Anson	
☐	4819159	April 1989	Shipley et al.	
☐	4871324	October 1989	Brune et al.	439/189
☐	5005122	April 1991	Griffin et al.	
☐	5134619	July 1992	Henson et al.	
☐	5140689	August 1992	Kobayashi	
☐	5151989	September 1992	Johnson et al.	

☐	5155729	October 1992	Rysko et al.	
☐	5157663	October 1992	Major et al.	
☐	5157771	October 1992	Losi et al.	
☐	5185693	February 1993	Loftis et al.	
☐	5210855	May 1993	Bartol	
☐	5210866	May 1993	Milligan et al.	
☐	5218697	June 1993	Chung	
☐	5227778	July 1993	Vacon et al.	
☐	5249293	September 1993	Schreiber et al.	
☐	5255367	October 1993	Bruckert et al.	
☐	5265098	November 1993	Mattson et al.	
☐	5271013	December 1993	Gleeson	
☐	5277615	January 1994	Hastings et al.	
☐	5287461	February 1994	Moore	
☐	5297067	March 1994	Blackborow et al.	
☐	5343358	August 1994	Hilbrink	361/700
☐	5343477	August 1994	Yamada	
☐	5369757	November 1994	Spiro et al.	
☐	5386567	January 1995	Lien et al.	710/103
☐	5390326	February 1995	Shah	
☐	5394526	February 1995	Crouse et al.	
☐	5408649	April 1995	Beshears et al.	
☐	5410691	April 1995	Taylor	
☐	5412723	May 1995	Canetti et al.	
☐	5423042	June 1995	Jalili et al.	
☐	5430876	July 1995	Schreiber et al.	
☐	5434994	July 1995	Shaheen et al.	
☐	5442749	August 1995	Northcutt et al.	
☐	5446736	August 1995	Gleeson et al.	
☐	5450578	September 1995	Mackenthun	
☐	5450583	September 1995	Inada	
☐	5452448	September 1995	Sakuraba et al.	
☐	5454080	September 1995	Fasig et al.	
☐	5455953	October 1995	Russell	
☐	5459863	October 1995	Taylor	
☐	5471099	November 1995	Larabell et al.	
☐	5471634	November 1995	Giorgio et al.	
☐	5475813	December 1995	Cieslak et al.	
☐	5479653	December 1995	Jones	
☐	5488716	January 1996	Schneider et al.	

☐	5502836	March 1996	Hale et al.
☐	5504882	April 1996	Chai et al.
☐	5513314	April 1996	Kandasamy et al.
☐	5517632	May 1996	Matsumoto et al.
☐	5518418	May 1996	Larabell
☐	5522031	May 1996	Ellis et al.
☐	5530905	June 1996	Nichols et al.
☐	5537642	July 1996	Glowny et al.
☐	5542087	July 1996	Neimat et al.
☐	5544339	August 1996	Baba
☐	5546583	August 1996	Shriver
☐	5548712	August 1996	Larson et al.
☐	5548724	August 1996	Akizawa et al.
☐	5564040	October 1996	Kubala
☐	5566297	October 1996	Devarakonda et al.
☐	5579222	November 1996	Bains et al.
☐	5579491	November 1996	Jeffries et al.
☐	5581552	December 1996	Civanlar et al.
☐	5592611	January 1997	Midgely et al.
☐	5600644	February 1997	Chang et al.
☐	5603029	February 1997	Aman et al.
☐	5604803	February 1997	Aziz
☐	5606719	February 1997	Nichols et al.
☐	5608865	March 1997	Midgely et al.
☐	5617540	April 1997	Civanlar et al.
☐	5621795	April 1997	Baker et al.
☐	5630007	May 1997	Kobayashi et al.
☐	5642515	June 1997	Jones et al.
☐	5644698	July 1997	Cannon
☐	5652908	July 1997	Douglas et al.
☐	5655152	August 1997	Ohnishi et al.
☐	5664106	September 1997	Caccavale
☐	5664119	September 1997	Jeffries et al.
☐	5675723	October 1997	Ekrot et al.
☐	5680538	October 1997	Jones et al.
☐	5692128	November 1997	Bolles et al.
☐	5694581	December 1997	Cheng
☐	5696965	December 1997	Dedrick
☐	5701406	December 1997	Matsumoto et al.
☐	5706458	January 1998	Koppolu

☐	5732137	March 1998	Aziz	
☐	5732240	March 1998	Caccavale	
☐	5734831	March 1998	Sanders	
☐	5734898	March 1998	He	
☐	5737549	April 1998	Hersch et al.	
☐	5737747	April 1998	Vishlitzky et al.	
☐	5740371	April 1998	Wallis	
☐	5740423	April 1998	Logan et al.	
☐	5784576	July 1998	Guthrie et al.	710/103
☐	5893140	April 1999	Vahalia et al.	711/118
☐	5966510	October 1999	Carbonneau et al.	714/44
☐	5974503	October 1999	Venkatesh et al.	714/6

FOREIGN PATENT DOCUMENTS

FOREIGN-PAT-NO	PUBN-DATE	COUNTRY	US-CL
0 653 759 A2	May 1995	EP	
0 709 779 A2	May 1996	EP	
0760503A1	March 1997	EP	
0 760 503 A1	March 1997	EP	

OTHER PUBLICATIONS

Copy of International Search Report Relating to PCT/US99/07284 Dated Sep. 01, 1999.

ART-UNIT: 211

PRIMARY-EXAMINER: Trammell; James P.

ASSISTANT-EXAMINER: Elisca; Pierre Eddy

ATTY-AGENT-FIRM: Fulwider, Patton Lee & Utecht

ABSTRACT:

The information server system provides a scalable expansion capability, due to the implementation of a unique mid-plane connector board for all components of the information server system that allows for multiply mirrored components to significantly improve fault tolerance of the server system. An integrated diagnostics monitoring subsystem eliminates the incompatability problems previously associated with performing diagnostics of the server system. A method is also provided for increasing the throughput rate of the user communications interface by installing a hash table database in the end user computer system to bypass a similar but slower function in the end user modem, to place the bulk of the transmission reception load on the main CPU, and synchronizing the modem with the transmission speed of the server unit.

18 Claims, 7 Drawing figures

☐ ░Generate Collection░ |Print|

L4: Entry 9 of 37   File: PGPB   Dec 19, 2002

DOCUMENT-IDENTIFIER: US 20020194548 A1
TITLE: Methods and apparatus for computer bus error termination

Summary of Invention Paragraph:
[0007] In one embodiment, the isolation control logic receives the device isolation signal from
system software. In another embodiment, for a system using virtual memory addressing, the
isolation control logic receives the device isolation signal from input/output virtual address
(IOVA) error detector detecting bus transactions addressing an invalid memory location. In
another embodiment, the isolation control logic receives the device isolation signal from
protocol checker logic monitoring the validity of the protocol for each of the bus
transactions. In yet another embodiment, the isolation control logic receives the device
isolation signal from a hot-plug sensor element responsive to the physical removal of the
device from its bus interface slot.

Detail Description Paragraph:
[0035] In one embodiment, a hot-plug sensor 48 is provided to sense the physical removal of the
device 32 from its bus interface slot. When the device 32 is extracted from its bus interface
slot the device 32 must be isolated from the bus as described herein to avoid causing a bus
fault. The sensor hot-plug 48 senses that the device 32 is being physically removed from its
bus interface slot. In response to sensing the physical removal of the device 32, the hot-plug
sensor 48 transmits the ISOLATE signal to the isolation control logic 36. The isolation control
logic 36 response to the ISOLATE signal by commanding the isolation of the device 32 from the
bus 12 as previously described.

☐ ▓▓▓ Generate Collection ▓▓▓ | Print |

L4: Entry 9 of 37   File: PGPB   Dec 19, 2002

PGPUB-DOCUMENT-NUMBER: 20020194548
PGPUB-FILING-TYPE: new
DOCUMENT-IDENTIFIER: US 20020194548 A1

TITLE: Methods and apparatus for computer bus error termination

PUBLICATION-DATE: December 19, 2002

INVENTOR-INFORMATION:
NAME   CITY   STATE   COUNTRY   RULE-47
Tetreault, Mark   Webster   MA   US

APPL-NO: 09/ 871180   [PALM]
DATE FILED: May 31, 2001

INT-CL: [07] H04 L 1/22

US-CL-PUBLISHED: 714/43
US-CL-CURRENT: 714/43

REPRESENTATIVE-FIGURES: 2

ABSTRACT:

In a computer system having a bus architecture, a system and process for isolating a device
from a bus without interrupting system operation is described, the system including bus
interface logic monitoring and reporting activity on the bus, isolation control logic receiving
error signals from error detectors, and isolation switches through which devices are
interconnected to the bus, the isolation switches allowing for the isolation of the devices
from the bus. The isolation control logic determines the devices to be isolated responsive to
the reported error and, in turn, transmits an isolation switch control signal to the isolation
switch(es) associated with the identified device(s) to isolate those device(s) from the bus. In
some embodiments, errors are reported by system software, input/output virtual address error
detectors for systems using virtual memory addressing, protocol error detectors, and sensors
sensing the physical removal of a bus-connected device from its bus interface slot.

Generate Collection   Print

L4: Entry 7 of 37   File: PGPB   Sep 9, 2004

DOCUMENT-IDENTIFIER: US 20040177202 A1
TITLE: Apparatus and method for generating hot-plug signal

Abstract Paragraph:
An apparatus and method for recognizing whether a medium is inserted into or removed from a
hot-plug apparatus and generating a hot-plug signal are provided. The hot-plug signal
generation apparatus includes a medium insertion unit, which receives a medium and generates a
sensor signal when the medium is inserted or removed; a medium control unit which controls the
received medium and generates the hot-plug signal; and a switch which outputs the hot-plug
signal in response to the sensor signal generated by the medium insertion unit. .

Summary of Invention Paragraph:
[0017] According to an exemplary aspect of the present invention, there is provided an
apparatus for generating a hot-plug signal comprising: a medium insertion/removal sensing unit
which senses when a medium is inserted or removed; and a hot-plug signal control unit which
outputs a hot-plug signal when the medium insertion/removal sensing unit senses that the medium
is inserted or removed.

Summary of Invention Paragraph:
[0018] According to another exemplary aspect of the present invention, an apparatus for
generating a hot-plug signal comprises: a medium insertion unit, which receives a medium and
generates a sensor signal when the medium is inserted or removed; a medium control unit which
controls the received medium and generates a hot-plug signal; and a switch which outputs the
hot-plug signal in response to the sensor signal generated by the medium insertion unit.

Summary of Invention Paragraph:
[0020] According to still another exemplary aspect of the present invention, there is provided
a method for generating a hot-plug signal comprising: (a) sensing when a medium is inserted or
removed; and (b) controlling a hot-plug signal to be output or not so that the hot-plug signal
is output when the medium is inserted or removed.

Summary of Invention Paragraph:
[0021] According to yet another exemplary aspect of the present invention, a method for
generating a hot-plug signal comprises: (a) generating a sensor signal when a medium is
inserted or removed; (b) controlling the medium and generating a hot-plug signal, and (c)
controlling a hot-plug signal to be output in response to the sensor signal.

Detail Description Paragraph:
[0030] The memory stick insertion unit 210, which is also referred to as a medium
insertion/removal sensing unit, is a portion into which a memory stick 250 is inserted and has
signal lines that are determined according to an interface with the memory stick 250. For
example, a pin number five of the memory stick 250 and a corresponding pin of the interface of
the memory stick insertion unit 210 become low upon insertion of the memory stick 250. This
connects the pin number five of the memory stick 250 to the switch 230 to switch a D+ or D-
signal of USB, thus generating a hot-plug signal. This uses a property of the memory stick 250
and the fact that a signal recognizing devices in USB is the D+ or D- signal.

Detail Description Paragraph:
[0033] In a case of a general external medium other than the memory stick, an apparatus for
generating a hot-plug signal may include a medium insertion/removal sensing unit and a hot-plug
signal control unit, wherein the medium insertion/removal sensing unit generates a signal when
it senses that the external medium is inserted or removed, and the hot-plug signal control unit
controls a hot-plug signal output according to the signal generated by the medium

insertion/removal sensing unit.

Detail Description Paragraph:
[0036] Then, the external medium is controlled and a hot-plug signal is generated (S320). The hot-plug signal may be a D+ or D- signal defined in a USB standard. Finally, an on/off operation of the hot-plug signal output is controlled in response to the sensor signal generated upon insertion/removal of the external medium (S330).

CLAIMS:

1. An apparatus for generating a hot-plug signal comprising: a medium insertion/removal sensing unit which senses when a medium is inserted or removed; and a hot-plug signal control unit which outputs a hot-plug signal when the medium insertion/removal sensing unit senses that the medium is inserted or removed.

2. An apparatus for generating a hot-plug signal comprising: a medium insertion unit, which receives a medium and generates a sensor signal when the medium is inserted or removed; a medium control unit which controls the received medium and generates a hot-plug signal; and a switch which outputs the hot-plug signal in response to the sensor signal generated by the medium insertion unit.

8. A method for generating a hot-plug signal comprising: (a) sensing when a medium is inserted or removed; and (b) controlling a hot-plug signal output so that the hot-plug signal is output when the medium is inserted or removed.

9. A method for generating a hot-plug signal comprising: (a) generating a sensor signal when a medium is inserted or removed; (b) controlling the medium and generating a hot-plug signal; and (c) controlling the hot-plug signal to be output in response to the sensor signal.

12. The method of claim 9, wherein in step (a), the sensor signal generated upon the insertion/removal of the medium is transferred to a switch for outputting the hot-plug signal.

15. A computer readable medium storing a computer program for executing a hot-plug signal generation method, the hot-plug signal generation method comprising: (a) sensing when a medium is inserted or removed; and (b) controlling a hot-plug signal output so that the hot-plug signal is output when the medium is inserted or removed.

16. A computer readable medium storing a computer program for executing a hot-plug signal generation method, the hot-plug signal generation method comprising: (a) generating a sensor signal by sensing whether a medium is inserted or removed; (b) controlling the medium and generating the hot-plug signal; and (c) controlling the hot-plug signal to be output in response to the sensor signal.

Refine Search

Search Results -

Terms	Documents
L2 and (710/301 |710/302 |710/303 |710/304).ccls.	13

Database:
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search: L8

Refine Search

Recall Text   Clear   Interrupt

Search History

DATE: Friday, July 01, 2005   Printable Copy   Create Case

Set Name Query	Hit Count	Set Name
side by side		result set
DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L8 L2 and 710/301-304.ccls.	13	L8
L7 L2 and 710/302-304.ccls.	7	L7
L6 L2 same 710/302-304.ccls.	0	L6
DB=EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR		
L5 L4	0	L5
DB=PGPB,USPT,USOC; PLUR=YES; OP=OR		
L4 L2 same hot	37	L4
L3 L2 same "hot-plug"	2	L3
L2 sens$3 near5 (insert$3 or remov$3) near10 signal	5598	L2
L1 sens$3 same (insert$3 or remov$3) same signal	69809	L1

END OF SEARCH HISTORY

☐ ▓▓▓ Generate Collection ▓▓▓ | Print |

L8: Entry 13 of 13   File: USPT   Jun 3, 1997

DOCUMENT-IDENTIFIER: US 5636347 A
TITLE: Computer card insertion detection circuit

Current US Original Classification (1):
710/302

CLAIMS:

1. A card insertion detection apparatus for providing a warning signal to a host system that a
circuit card is in the process of being inserted into a card slot of the host system in order
to allow the host system to accept the circuit card in an orderly manner that does not
adversely affect the host system by protecting the host system from transients that could
result from the connection of the circuit card, the circuit card having a connector with a
multiplicity of terminals distributed along the connector's width, and arranged in at least one
row, for connecting to corresponding terminals of a mating connector in a host system card
slot, the circuit card connector having a group of preassigned ground terminals located near
both edges of the connector width, a subset of the group of ground terminals located near both
edges being card insertion detection terminals to be used for card insertion detection, the
apparatus comprising:

(a) a card slot connector with connector terminals for mating the card slot connector terminals
with a circuit card connector terminals;

(b) detection circuitry connected to a subset of the card slot connector terminals
corresponding to the card insertion detection terminals of the card slot connector for
generating the warning signal indicating the onset of a circuit card insertion by sensing the
grounding of at least one terminal of the card slot connector terminals; and

(c) grounding circuitry that grounds at least one card insertion detection terminal after the
circuit card insertion is detected.

9. A system for detecting an insertion of a circuit card into a host system and for providing
the host system with a warning signal that the circuit card is in the process of being inserted
into the host system to allow the host system to accept the circuit card in an orderly manner
that does not adversely affect the host system by protecting the host system from transients
that could result from connection of the circuit card,

the circuit card comprising:

a connector having a multiplicity of terminals distributed along the width of a circuit card
connector; and arranged in at least one row, for connecting to the corresponding terminals of a
mating connector in a host system card slot; and

a group of preassigned ground terminals located near both edges of the connector width, a
subset of the group of ground terminals located near both edges being card insertion detection
terminals to be used for card insertion detection;

the host system comprising:

a card slot for the insertion of the circuit card, the card slot having the mating connector
containing terminals to mate with the circuit card;

detection circuitry connected to a subset of the card slot connector terminals corresponding to the card insertion detection terminals of the card slot connector for generating the warning signal indicating the onset of a circuit card insertion by sensing the grounding of at least one terminal of the card slot connector terminals; and

grounding circuitry that grounds at least one card insertion detection terminal after the circuit card insertion is detected.

10. A means for providing a warning signal to a host system upon detection of a circuit card being inserted into a card slot of the host system in order to allow the host system to accept the circuit card in an orderly manner that does not adversely affect the host system by protecting the host system from transients that could result from the connection of the circuit card, the circuit card having a connector with a multiplicity of terminals distributed along the connector's width, and arranged in at least one row, for connecting to corresponding terminals of a mating connector in a host system card slot, the circuit card connector having a group of preassigned ground terminals located near both edges of the connector width, a subset of the group of ground terminals located near both edges being card insertion detection terminals to be used for card insertion detection, the means for detection comprising:

(a) a means for mating the host system card slot connector terminals with the circuit card connector terminals;

(b) detection means connected to a subset of the card slot connector terminals corresponding to the card insertion detection terminals of the card slot connector for generating the warning signal indicating the onset of a circuit card insertion by sensing the grounding of at least one terminal of the card slot connector terminals; and

(c) grounding means that grounds at least one card insertion detection terminal after the circuit card insertion is detected.

13. A card insertion detection apparatus for providing a warning signal to a host system that a circuit card is in the process of being inserted into a card slot of the host system in order to allow the host system to accept the circuit card in an orderly manner that does not adversely affect the host system by protecting the host system from transients that could result from the connection of the circuit card, the circuit card having a connector with a multiplicity of terminals distributed along the connector's width, and arranged in at least one row, for connecting to corresponding terminals of a mating connector in a host system card slot, the circuit card connector having a group of preassigned ground terminals located near both edges of the connector width and a group of preassigned insertion detection terminals located near both edges to be used for card insertion detection, the apparatus comprising:

(a) a card slot connector with connector terminals for mating the card slot connector terminals with a circuit card connector terminals;

(b) detection circuitry connected to the card insertion detection terminals of the card slot connector for generating the warning signal indicating the onset of a circuit card insertion by sensing the grounding of at least one terminal of the card slot connector terminals; and

(c) grounding circuitry that grounds at least one card insertion detection terminal after the circuit card insertion is detected.

☐   Generate Collection | Print

L8: Entry 13 of 13   File: USPT   Jun 3, 1997

US-PAT-NO: 5636347
DOCUMENT-IDENTIFIER: US 5636347 A

TITLE: Computer card insertion detection circuit

DATE-ISSUED: June 3, 1997

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Muchnick; Michael J.	Fair Oaks	CA		
Verseput; Jerry A.	Folsom	CA		
Ajanovic; Jasmin	Folsom	CA		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Intel Corporation	Santa Clara	CA			02

APPL-NO: 08/ 733335   [PALM]
DATE FILED: October 17, 1996

PARENT-CASE:
This is a continuation of application Ser. No. 08/313,454, filed Sep. 24, 1994, now abandoned.

INT-CL: [06] G06 F 13/20

US-CL-ISSUED: 395/283; 395/282
US-CL-CURRENT: 710/302

FIELD-OF-SEARCH: 395/282, 395/283

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

Search Selected | Search ALL | Clear

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4245270	January 1981	Busby	361/58
☐	5210855	May 1993	Bartol	395/500
☐	5268592	December 1993	Bellamy et al.	307/43
☐	5317697	May 1994	Husak et al.	395/500
☐	5410717	April 1995	Floro	395/800

ART-UNIT: 235

PRIMARY-EXAMINER: Ray; Gopal C.

ASSISTANT-EXAMINER: Seto; Jeffrey K.

ATTY-AGENT-FIRM: Blakely, Sokoloff, Taylor & Zafman

ABSTRACT:

A personal computer (PC) card insertion method and apparatus uses a subset of connector ground terminals and pins, located at either end of the connector, for detecting the onset of a card insertion. The host PC card slot connector has pull-up resistors for keeping the subset of ground terminals at a high logic level (V.sub.CC). Also, the subset of pins are made longer than the signal pins so that when an insertion of a PC card begins, the grounding of one or more of the subset of pins indicates that a PC card insertion has begun, allowing the host system to take the necessary precautions to ensure an orderly acceptance of the card without any undesirable system affects that might otherwise result. Also, a logic network for using the subset of connector terminals as additional grounding connections is provided upon completion of the insertion.

15 Claims, 11 Drawing figures

L8: Entry 11 of 13   File: USPT   Nov 21, 2000

DOCUMENT-IDENTIFIER: US 6151647 A
TITLE: Versatile interface smart card

Detailed Description Text (10):
The reader 16 has a slot 26 that is appropriately dimensioned to receive the card 18. The bottom of the slot has a switch 28, or other form of sensor, to detect when the card is fully inserted into the slot. The interior surface of the slot has a set of mating contacts (not shown), which engage corresponding contacts 20 on the card when it is fully inserted. When the sensor detects that a card is completely inserted into the slot 26 of the reader, it sends a signal which causes the reader to initiate a power-up procedure, described in detail hereinafter.

Current US Original Classification (1):
710/301

☐ [Generate Collection] [Print]

L8: Entry 11 of 13   File: USPT   Nov 21, 2000

US-PAT-NO: 6151647
DOCUMENT-IDENTIFIER: US 6151647 A

TITLE: Versatile interface smart card

DATE-ISSUED: November 21, 2000

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Sarat; Jean-Marc	Belmont	CA		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Gemplus				FR	03

APPL-NO: 09/ 048009   [PALM]
DATE FILED: March 26, 1998

INT-CL: [07] G06 F 13/00

US-CL-ISSUED: 710/103; 710/11, 710/102, 710/104, 710/105
US-CL-CURRENT: 710/301; 710/104, 710/105, 710/11

FIELD-OF-SEARCH: 710/103, 710/102, 710/104, 710/105, 710/129, 710/62, 710/8, 710/11

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

[Search Selected] [Search ALL] [Clear]

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	5581708	December 1996	Iijima	709/213
☐	5594233	January 1997	Kenneth et al.	235/492
☐	5613159	March 1997	Colnot	710/11
☐	5638530	June 1997	Pawate et al.	711/115
☐	5679945	October 1997	Renner et al.	235/492
☐	5721781	February 1998	Deo et al.	380/25
☐	5832240	November 1998	Larsen et al.	710/105

ART-UNIT: 271

PRIMARY-EXAMINER: Etienne; Ario

ATTY-AGENT-FIRM: Burns, Doane, Swecker & Mathis, L.L.P.

ABSTRACT:

A smart card that is compatible with multiple different protocols includes a standard set of
contacts that comply with the protocols of a published standard, and another contact not
designated by the standard which is used to indicate whether the card is to operate in a non-
standard mode. When the card is to operate in the non-standard mode, a simple start-up
procedure is employed which does not require strict timing constraints, enabling a less
expensive interface device to be used. The interface device can be connected to any bus of a
computer which operates in accordance with a desired non-standard protocol. Due to the
flexibility and functionality offered by smart cards that have microprocessors incorporated
therein, the multi-protocol smart card can be used to drive, or otherwise communicate with, any
of a variety of peripheral devices, whether or not a personal computer is present in the
system.

31 Claims, 9 Drawing figures

☐ ▓▓▓ Generate Collection ▓▓▓ | Print

L8: Entry 6 of 13   File: USPT   Jul 20, 2004

DOCUMENT-IDENTIFIER: US 6766469 B2
TITLE: Hot-replace of memory

Current US Cross Reference Classification (1):
710/302

CLAIMS:

16. The method of replacing a memory module in a computer system, as set forth in claim 15, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

32. The method of replacing a memory module in a computer system, as set forth in claim 31, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

49. The method of replacing a memory module in a computer system, as set forth in claim 48, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

60. The method of replacing a memory module in a computer system, as set forth in claim 59, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

L8: Entry 6 of 13   File: USPT   Jul 20, 2004

US-PAT-NO: 6766469
DOCUMENT-IDENTIFIER: US 6766469 B2

TITLE: Hot-replace of memory

DATE-ISSUED: July 20, 2004

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Larson; John E.	Houston	TX		
MacLaren; John M.	Cypress	TX		
Johnson; Jerome J.	Spring	TX		
Piccirillo; Gary J.	Cypress	TX		
Lester; Robert A.	Tomball	TX		
Post; Christian H.	Spring	TX		
Galloway; Jeffery	The Woodlands	TX		
Anand; Anisha	Houston	TX		
Lai; Ho M.	Spring	TX		
Rose; Eric	Austin	TX		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Hewlett-Packard Development Company, L.P.	Houston	TX			02

APPL-NO: 09/ 769783   [PALM]
DATE FILED: January 25, 2001

PARENT-CASE:
CROSS-REFERENCE TO RELATED APPLICATIONS This application claims priority to Provisional
Application Ser. No. 60/177,952, filed on Jan. 25, 2000.

INT-CL: [07] G06 F 11/00

US-CL-ISSUED: 714/7; 714/5, 711/115, 710/302
US-CL-CURRENT: 714/7; 710/302, 711/115, 714/5

FIELD-OF-SEARCH: 714/7, 714/5, 714/3, 711/115, 439/924.1, 439/924.2, 710/302

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

            Search Selected   Search ALL   Clear

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	5313626	May 1994	Jones et al.	395/575

☐	5331646	July 1994	Krueger et al.	371/40.1
☐	5367669	November 1994	Holland et al.	395/575
☐	5636347	June 1997	Muchnick et al.	710/302
☐	6098132	August 2000	Olarig et al.	710/103
☐	6223301	April 2001	Santeler et al.	714/6
☐	6549969	April 2003	Hsu et al.	710/304
☐	6651138	November 2003	Lai et al.	711/115
☐	6684292	January 2004	Piccirillo et al.	711/106
☐	6700829	March 2004	Abe et al.	365/226
☐	2004/0030952	February 2004	Piccirillo et al.	714/7

ART-UNIT: 2184

PRIMARY-EXAMINER: Beausoliel; Robert

ASSISTANT-EXAMINER: Duncan; Marc M

ABSTRACT:

A method of replacing a memory module in a computer system. Specifically, a method for replacing a memory module in a segment of a redundant memory system, without powering-down the memory system.

63 Claims, 8 Drawing figures

Previous Doc   Next Doc   Go to Doc#

File Edit View Tools Window Help

```
US-PAT-NO:              6854070

DOCUMENT-IDENTIFIER:    US 6854070 B2

TITLE:                  Hot-upgrade/hot-add memory


----------- KWIC -----------

Detailed Description Text - DETX (32):
    The insertion/removal sensor (IRS) may utilize a pin 118A and a pin 118B to
detect when a memory cartridge 25 is being installed or removed.  For example,
the pin 118A may be made shorter relative to the pin 118B.  Additionally, the
pin 118B may be made longer than the pins 118C and shorter than the pins 118D
and 118E.  Thus, during insertion of a memory cartridge 25, the pin 118B will
come into contact with a female socket 114B before pins 118A and 118C, but
after pins 118D and 118E come into contact with their respective female
counterparts.  Additionally, during removal of a memory cartridge 25, pin 118B
will remain in contact with a female socket 114B longer than pins 118A or 118C.
This information may be used by the system 10 to determine when installation or
removal of a cartridge 25 has started and when it has been completed.  By
varying the lengths of the pins 118A-118E, the sequence of signal
initialization can be controlled during a hot-plug insertion or removal event.
```

US006854070B2

(12) **United States Patent**
Johnson et al.

(10) Patent No.: US 6,854,070 B2
(45) Date of Patent: Feb. 8, 2005

(54) HOT-UPGRADE/HOT-ADD MEMORY

(75) Inventors: Jerome J. Johnson, Spring, TX (US);
John M. MacLaren, Cypress, TX
(US); Robert A. Lester, Tomball, TX
(US); John E. Larson, Houston, TX
(US); Gary J. Piccirillo, Cypress, TX
(US); Christian H. Post, Spring, TX
(US); Jeffrey Galloway, The
Woodlands, TX (US); Ho M. Lai,
Spring, TX (US); Anisha Anand,
Houston, TX (US); Eric Rose, Austin,
TX (US)

(73) Assignee: Hewlett-Packard Development
Company, L.P., Houston, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 596 days.

(21) Appl. No.: 09/769,978

(22) Filed: Jan. 25, 2001

(65) Prior Publication Data
US 2002/0010875 A1 Jan. 24, 2002

Related U.S. Application Data

(60) Provisional application No. 60/177,811, filed on Jan. 25, 2000.

(51) Int. Cl.⁷ G06F 11/00
(52) U.S. Cl. 714/5; 714/7; 710/302;
711/115
(58) Field of Search 714/5, 6, 7, 36,
714/42, 54; 711/115; 710/104, 301, 302

(56) **References Cited**

U.S. PATENT DOCUMENTS

|			
5,313,626 A	5/1994	Jones et al.	395/575
5,331,646 A	7/1994	Krueger et al.	371/40.1
5,367,669 A	11/1994	Holland et al.	395/575
5,289,587 A	2/1995	Linn et al.	711/100
5,491,804 A *	2/1996	Heath et al.	710/7
5,581,712 A	12/1996	Herman	710/302
5,636,342 A *	6/1997	Michelik et al.	710/302
5,784,576 A *	7/1998	Guthrie et al.	710/302
6,058,153 A	5/2000	Glady et al.	710/103
6,223,301 B1	4/2001	Santeler et al.	714/6
6,457,623 B1 *	11/2001	Emerson et al.	710/302
6,604,252 B1 *	8/2002	Barli et al.	710/15

* cited by examiner

Primary Examiner—Dieu-Minh Le

(57)   **ABSTRACT**

A method of adding memory capacity to a computer system.
The computer system comprises a redundant memory sys-
tem including a plurality of memory cartridges. By
powering-down a memory cartridge, adding an additional
memory module to the memory cartridge, and powering-up
the memory cartridge for each memory cartridge in the
system, the system can transition from a redundant mode of
operation to a non-redundant mode of operation for each
power-down, thus allowing the computer system to remain
functional during the addition of the memory module.
Alternatively, memory cartridges with higher memory
capacity than those currently present in the computer system
can be used to replace existing memory cartridges in the
computer system, using the same techniques.

56 Claims, 7 Drawing Sheets

File   Edit   View   Tools   Window   Help

US-PAT-NO: 6766469

DOCUMENT-IDENTIFIER: US 6766469 B2

TITLE: Hot-replace of memory

---------- KWIC ----------

Detailed Description Text - DETX (32):
    The insertion/removal sensor (IRS) may utilize a pin 118A and a pin 118B to
detect when a memory cartridge 25 is being installed or removed. For example,
the pin 118A may be made shorter relative to the pin 118B. Additionally, the
pin 118B may be made longer than the pins 118C and shorter than the pins 118D
and 118E. Thus, during insertion of a memory cartridge 25, the pin 118B will
come into contact with a female socket 114B before pins 118A and 118C, but
after pins 118D and 118E come into contact with their respective female
counterparts. Additionally, during removal of a memory cartridge 25, pin 118B
will remain in contact with a female socket 114B longer than pins 118A or 118C.
This information may be used by the system 10 to determine when installation or
removal of a cartridge 25 has started and when it has been completed. By
varying the lengths of the pins 118A-118E, the sequence of signal
initialization can be controlled during a hot-plug insertion or removal event.

Hit List

Search Results - Record(s) 1 through 7 of 7 returned.

☐ 1. Document ID: US 6266724 B1

L1: Entry 1 of 7   File: USPT   Jul 24, 2001

US-PAT-NO: 6266724
DOCUMENT-IDENTIFIER: US 6266724 B1

TITLE: Removable mother/daughter peripheral card

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 2. Document ID: US 6131134 A

L1: Entry 2 of 7   File: USPT   Oct 10, 2000

US-PAT-NO: 6131134
DOCUMENT-IDENTIFIER: US 6131134 A

TITLE: Hot plug-and-play converter of a universal serial bus interface

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 3. Document ID: US 5721669 A

L1: Entry 3 of 7   File: USPT   Feb 24, 1998

US-PAT-NO: 5721669
DOCUMENT-IDENTIFIER: US 5721669 A

TITLE: Gear-driven docking apparatus for removable mass-storage drives

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐ 4. Document ID: US 5717571 A

L1: Entry 4 of 7   File: USPT   Feb 10, 1998

US-PAT-NO: 5717571
DOCUMENT-IDENTIFIER: US 5717571 A

TITLE: Mechanism locking removable module into computer

| Full | Title | Citation | Front | Review | Classification | Date | Reference | | | Claims | KWIC | Draw Desc | Image |

☐   5.   Document ID: US 5045960 A

L1: Entry 5 of 7   File: USPT   Sep 3, 1991

US-PAT-NO: 5045960
DOCUMENT-IDENTIFIER: US 5045960 A

TITLE: Self-aligning guide and track for removable disk drive module

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐   6.   Document ID: US 5010426 A

L1: Entry 6 of 7   File: USPT   Apr 23, 1991

US-PAT-NO: 5010426
DOCUMENT-IDENTIFIER: US 5010426 A

TITLE: Installation mechanism for removable computer drive module

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

☐   7.   Document ID: US 4941841 A

L1: Entry 7 of 7   File: USPT   Jul 17, 1990

US-PAT-NO: 4941841
DOCUMENT-IDENTIFIER: US 4941841 A

TITLE: Adapter and a removable slide-in cartridge for an information storage system

Full	Title	Citation	Front	Review	Classification	Date	Reference			Claims	KWIC	Draw Desc	Image

Clear	Generate Collection	Print	Fwd Refs	Bkwd Refs	Generate OACS

Terms	Documents
4941841.pn. or 5010426.pn. or 5045960.pn. or 5717571.pn. or 5721669.pn. or 6266724.pn. or 6131134.pn.	7

Display Format: TI   [Change Format]

Previous Page   Next Page   Go to Doc#

☐ ▒▒▒ Generate Collection ▒▒▒ | Print |

L6: Entry 1 of 26   File: USPT   May 10, 2005

DOCUMENT-IDENTIFIER: US 6892271 B2
TITLE: Memory module resync

Detailed Description Text (30):
In the illustrated embodiment, the memory hot plug interface 110 utilizes various inputs and
programmable array logic (PAL) devices 112 to control power to each memory segment 24,
illustrated as memory cartridges 25 in FIG. 5. The PAL arrangement 112 receives input from
several sources. In the illustrated embodiment, female pins 114A-114E on a cartridge connector
116, which may reside on the memory cartridge 25, are configured to engage male pins 118A-118E
on a memory control board 120. Each pin connection provides an electrical path to exchange data
and control signals between the memory cartridge 25 and the memory control board 120. For
example, an insertion/removal sensor (IRS) and a pre-insertion/removal notification sensor
(PIRN) are used to provide inputs to the system.

Detailed Description Text (33):
The insertion/removal sensor (IRS) may utilize a pin 118A and a pin 118B to detect when a
memory cartridge 25 is being installed or removed. For example, the pin 118A may be made
shorter relative to the pin 118B. Additionally, the pin 118B may be made longer than the pins
118C and shorter than the pins 118D and 118E. Thus, during insertion of a memory cartridge 25,
the pin 118B will come into contact with a female socket 114B before pins 118A and 118C, but
after pins 118D and 118E come into contact with their respective female counterparts.
Additionally, during removal of a memory cartridge 25, pin 118B will remain in contact with a
female socket 114B longer than pins 118A or 118C. This information may be used by the system 10
to determine when installation or removal of a cartridge 25 has started and when it has been
completed. By varying the lengths of the pins 118A-118E, the sequence of signal initialization
can be controlled during a hot-plug insertion or removal event.

Current US Cross Reference Classification (1):
710/302

Previous Doc   Next Doc   Go to Doc#

L6: Entry 3 of 26   File: USPT   Feb 8, 2005

DOCUMENT-IDENTIFIER: US 6854070 B2
TITLE: Hot-upgrade/hot-add memory

Detailed Description Text (29):
In the illustrated embodiment, the memory hot plug interface 110 utilizes various inputs and programmable array logic (PAL) devices 112 to control power to each memory segment 24, illustrated as memory cartridges 25 in FIG. 5. The PAL arrangement 112 receives input from several sources. In the illustrated embodiment, female pins 114A-114E on a cartridge connector 116, which may reside on the memory cartridge 25, are configured to engage male pins 118A-118E on a memory control board 120. Each pin connection provides an electrical path to exchange data and control signals between the memory cartridge 25 and the memory control board 120. For example, an insertion/removal sensor (IRS) and a pre-insertion/removal notification sensor (PIRN) are used to provide inputs to the system.

Detailed Description Text (32):
The insertion/removal sensor (IRS) may utilize a pin 118A and a pin 118B to detect when a memory cartridge 25 is being installed or removed. For example, the pin 118A may be made shorter relative to the pin 118B. Additionally, the pin 118B may be made longer than the pins 118C and shorter than the pins 118D and 118E. Thus, during insertion of a memory cartridge 25, the pin 118B will come into contact with a female socket 114B before pins 118A and 118C, but after pins 118D and 118E come into contact with their respective female counterparts. Additionally, during removal of a memory cartridge 25, pin 118B will remain in contact with a female socket 114B longer than pins 118A or 118C. This information may be used by the system 10 to determine when installation or removal of a cartridge 25 has started and when it has been completed. By varying the lengths of the pins 118A-118E, the sequence of signal initialization can be controlled during a hot-plug insertion or removal event.

Current US Cross Reference Classification (1):
710/302

CLAIMS:

27. The method of increasing the memory capacity in a computer system, as set forth in claim 26, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

50. The method of increasing the memory capacity in a computer system, as set forth in claim 49, wherein the act of connecting the one or more first insertion removal sense pins causes the assertion of a power signal to a power controller.

☐ ▓▓Generate Collection▓▓ | Print |

L6: Entry 3 of 26   File: USPT   Feb 8, 2005

US-PAT-NO: 6854070
DOCUMENT-IDENTIFIER: US 6854070 B2

TITLE: Hot-upgrade/hot-add memory

DATE-ISSUED: February 8, 2005

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Johnson; Jerome J.	Spring	TX		
MacLaren; John M.	Cypress	TX		
Lester; Robert A.	Tomball	TX		
Larson; John E.	Houston	TX		
Piccirillo; Gary J.	Cypress	TX		
Post; Christian H.	Spring	TX		
Galloway; Jeffery	The Woodlands	TX		
Lai; Ho M.	Spring	TX		
Anand; Anisha	Houston	TX		
Rose; Eric	Austin	TX		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Hewlett-Packard Development Company, L.P.	Houston	TX			02

APPL-NO: 09/ 769978   [PALM]
DATE FILED: January 25, 2001

PARENT-CASE:
CROSS-REFERENCE TO RELATED APPLICATIONS This application claims priority to Provisional
Application Ser. No. 60/177,812, filed on Jan. 25, 2000. The following commonly owned
applications and patents are hereby incorporated by reference for all purposes: U.S. patent
application Ser. No. 08/940,419, filed Sep. 30, 1997, entitled "Installation and Removal of
Components of a Computer" by Sompong P. Olarig, Kenneth A. Jansen, and Paul A. Sander, issued
Aug. 1, 2000, as U.S. Pat. No. 6,098,132; U.S. patent application Ser. No. 08/940,282, filed
Sep. 30, 1997, entitled "Fault Tolerant Memory" by Paul A. Santler, Kenneth A. Jansen, and
Sompong P. Olarig. U.S. patent application Ser. No. 09/303,369, filed Apr. 30, 1999, entitled
"Replacement, Upgrade and/or Additional of Hot-Pluggable Components in a Computer System" by
Theodore F. Emerson, Vincent Nguyen, Peter Michels, and Steve Clohset; and U.S. patent
application Ser. No. 09/769,956, filed Jan. 25, 2001, entitled "Memory Sub-System Error
Cleansing" by William J. Walker, and John M. MacLaren; U.S. patent application Ser. No
09/769,716, filed Jan. 25, 2001, entitled "Hot Replace Power Control Sequence Logic" by John M.
MacLaren, Jerome J. Johnson, Robert A. Lester, Gary J. Piccirillo, John E. Larson, and
Christian H. Post; U.S. patent application Ser. No. 09/769,783, filed Jan. 25, 2001, entitled
"Hot-Replace of Memory" by John E. Larson, John M. MacLaren, Jerome J. Johnson, Gary J.
Piccirillo, Robert A. Lester, Christian H. Post, Jefferey Galloway, Anisha Anand, Ho M. Lai,
and Eric Rose; U.S. patent application Ser. No. 09/769,978, filed Jan. 25, 2001, entitled "Hot-
Upgrade/Hot-Add Memory" by Jerome J. Johnson, John M. MacLaren, Robert A. Lester, John E.
Larson, Gary J. Piccirillo, Christian H. Post, Jeffery Galloway, Ho M. Lai, Anisha Anand, and
Eric Rose; U.S. patent application Ser. No. 09/769,957, filed Jan. 25, 2001, entitled "Raid
Memory" by John M. MacLaren, Paul Santeler, Kenneth A. Jansen, Sompong P. Olarig, Robert A.

Lester, Patrick L. Ferguson, John E. Larson, Jerome J. Johnson, and Gary J. Piccirillo; U.S. patent application Ser. No. 09/769,833, filed Jan. 25, 2001, entitled "Technique for Identifying Multiple Circuit Components" by John M. MacLaren and John E. Larson; U.S. patent application Ser. No. 09/769,958, filed Jan. 25, 2001, entitled "Memory Data Verify Operation" by Robert A. Lester, John M. MacLaren, Patrick L. Ferguson, and John E. Larson; U.S. patent application Ser. No. 09/769,959, filed Jan. 25, 2001, entitled "Real-Time Hardware Memory Scrubbing" by John E. Larson, John M. MacLaren, Robert A. Lester, Gary Piccirillo, Jerome J. Johnson, and Patrick L. Ferguson; U.S. patent application Ser. No. 09/770,101, filed Jan. 25, 2001, entitled "Hot-Plug Memory Cartridge Power Control Logic" by Ho M. Lai and John M. MacLaren; U.S. patent application Ser. No. 09/770,100, filed Jan. 25, 2001, entitled "Removable Memory Cartridge System for Use With a Server or Other Processor-Based Device" by Brett D. Roscoe, George D. Megason, and Christian H. Post.

INT-CL: [07] G06F01100

US-CL-ISSUED: 714/5; 714/7, 710/302, 711/115
US-CL-CURRENT: 714/5; 710/302, 711/115, 714/7

FIELD-OF-SEARCH: 714/5, 714/6, 714/7, 714/36, 714/42, 714/54, 711/115, 710/104, 710/301, 710/302

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

[Search Selected] [Search ALL] [Clear]

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	5313626	May 1994	Jones et al.	395/575
☐	5331646	July 1994	Krueger et al.	371/40.1
☐	5367669	November 1994	Holland et al.	395/575
☐	5386567	January 1995	Lien et al.	713/100
☐	5491804	February 1996	Heath et al.	710/7
☐	5581712	December 1996	Herrman	710/302
☐	5636347	June 1997	Muchnick et al.	710/302
☐	5784576	July 1998	Guthrie et al.	710/302
☐	6098132	August 2000	Olarig et al.	710/103
☐	6223301	April 2001	Santeler et al.	714/6
☐	6487623	November 2002	Emerson et al.	710/302
☐	6604152	August 2003	Bard et al.	710/16

ART-UNIT: 2114

PRIMARY-EXAMINER: Le; Dieu-Minh

ABSTRACT:

A method of adding memory capacity to a computer system. The computer system comprises a redundant memory system including a plurality of memory cartridges. By powering-down a memory cartridge, adding an additional memory module to the memory cartridge, and powering-up the memory cartridge for each memory cartridge in the system, the system can transition from a

redundant mode of operation to a non-redundant mode of operation for each power-down, thus allowing the computer system to remain functional during the addition of the memory module. Alternatively, memory cartridges with higher memory capacity than those currently present in the computer system can be used to replace existing memory cartridges in the computer system, using the same techniques.

56 Claims, 8 Drawing figures

☐ ▒▒▒ Generate Collection ▒▒▒ | Print

L6: Entry 17 of 26   . File: USPT   Mar 6, 2001

DOCUMENT-IDENTIFIER: US 6199128 B1
TITLE: Smart card system for use with peripheral devices

Detailed Description Text (10):
The reader 16 has a slot 26 that is appropriately dimensioned to receive the card 18. The bottom of the slot has a switch 28, or other form of sensor, to detect when the card is fully inserted into the slot. The interior surface of the slot has a set of mating contacts (not shown), which engage corresponding contacts 20 on the card when it is fully inserted. When the sensor detects that a card is completely inserted into the slot 26 of the reader, it sends a signal which causes the reader to initiate a power-up procedure, described in detail hereinafter.

Current US Original Classification (1):
710/301

☐ ▓ Generate Collection ▓ | Print |

L6: Entry 17 of 26   File: USPT   Mar 6, 2001

US-PAT-NO: 6199128
DOCUMENT-IDENTIFIER: US 6199128 B1

TITLE: Smart card system for use with peripheral devices

DATE-ISSUED: March 6, 2001

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Sarat; Jean-Marc	Belmont	CA		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Gemplus, S.C.A.				FR	03

APPL-NO: 09/ 048010   [PALM]
DATE FILED: March 26, 1998

INT-CL: [07] G06 F 13/00

US-CL-ISSUED: 710/102; 710/129, 710/2, 710/72
US-CL-CURRENT: 710/301; 710/2, 710/72

FIELD-OF-SEARCH: 235/25, 235/380-386, 235/492, 380/25, 380/23, 710/1-14, 710/36-51, 710/72-74,
710/100-106, 710/126-131

PRIOR-ART-DISCLOSED:

                              U.S. PATENT DOCUMENTS

              ▓ Search Selected ▓   ▓ Search ALL ▓   ▓ Clear ▓

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4985920	January 1991	Seki	380/23
☐	5093862	March 1992	Scwartz	380/25
☐	5434395	July 1995	Storck et al.	235/380
☐	5521362	May 1996	Powers	235/380
☐	5721781	February 1998	Deo et al.	380/25
☐	5729004	March 1998	Kim et al.	235/492
☐	5834756	November 1998	Gutman et al.	235/493
☐	5841868	November 1998	Helbig, Sr.	380/25
☐	5852290	December 1998	Chaney	235/492
☐	6012634	January 2000	Brogan et al.	235/380

ART-UNIT: 272

PRIMARY-EXAMINER: Shin; Christopher B.

ATTY-AGENT-FIRM: Burns, Doane, Swecker & Mathis, L.L.P.

ABSTRACT:

A smart card that is compatible with multiple different protocols includes a standard set of contacts that comply with the protocols of a published standard, and another contact not designated by the standard which is used to indicate whether the card is to operate in a non-standard mode. When the card is to operate in the non-standard mode, a simple start-up procedure is employed which does not require strict timing constraints, enabling a less expensive interface device to be used. The interface device can be connected to any bus of a computer which operates in accordance with a desired non-standard protocol. Due to the flexibility and functionality offered by smart cards that have microprocessors incorporated therein, the multi-protocol smart card can be used to drive, or otherwise communicate with, any of a variety of peripheral devices, whether or not a personal computer is present in the system.

24 Claims, 9 Drawing figures

☐ ░░░Generate Collection░░░ | Print |

L1: Entry 5 of 5   File: USPT   Aug 27, 2002

DOCUMENT-IDENTIFIER: US 6442734 B1
** See image for Certificate of Correction **
TITLE: Method and apparatus for detecting the type of interface to which a peripheral device is
connected

Detailed Description Text (26):
Switch controller 146 then turns on switch 150 to enable pull-up resistor 154. It should be
noted that the particular pull-up resistor enabled at this point is that pull-up resistor which
is connected to the PS2 data conductor and the USB D+ conductor for a high-speed USB device, or
the PS2 data conductor and the USB D- conductor for a low-speed USB device. The flow diagram
illustrated in FIG. 4 illustrates operation of the PS2/high-speed USB peripheral device.

Detailed Description Text (36):
Microcontroller 202 also includes USB differential data outputs D+ and D- provided on pins 226
and 228. The D+ and D- pins 226 and 228 are coupled to conductors which represent USB D+ and
USB D- signals for a high-speed USB device, and PS2 data and PS2 clock signals, respectively,
for a PS2 device.

Detailed Description Text (48):
As with FIG. 4, the signals mentioned in FIG. 6 can be combined differently such that either
the PS2 data or PS2 clock signals can be associated with either the USB D+ or USB D- signals.
This type of system is contemplated to be within one illustrative embodiment of the present
invention.

☐ ▨▨▨ Generate Collection ▨▨▨ | Print |

L1: Entry 5 of 5   File: USPT   Aug 27, 2002

US-PAT-NO: 6442734
DOCUMENT-IDENTIFIER: US 6442734 B1
** See image for **Certificate of Correction** **

TITLE: Method and apparatus for detecting the type of interface to which a peripheral device is connected

DATE-ISSUED: August 27, 2002

INVENTOR-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY
Hanson; Mark T.	Lynnwood	WA		
Sherman; Nathan C.	Redmond	WA		

ASSIGNEE-INFORMATION:

NAME	CITY	STATE	ZIP CODE	COUNTRY	TYPE CODE
Microsoft Corporation	Redmond	WA			02

APPL-NO: 09/ 410413   [PALM]
DATE FILED: October 1, 1999

PARENT-CASE:
REFERENCE TO CO-PENDING APPLICATION This is a continuation-in-part of the application Ser. No. 09/112,171, filed Jul. 8, 1998 entitled "METHOD AND APPARATUS FOR DETECTING THE TYPE OF INTERFACE TO WHICH A PERIPHERAL DEVICE IS CONNECTED" and assigned the same assignee as the present invention.

INT-CL: [07] G06 F 17/50

US-CL-ISSUED: 716/4
US-CL-CURRENT: 716/4

FIELD-OF-SEARCH: 710/129, 710/100, 710/15, 710/63, 710/62, 710/110, 710/8, 326/30, 360/69, 708/854, 713/400, 716/1, 716/4, 716/5, 716/6, 716/12

PRIOR-ART-DISCLOSED:

U.S. PATENT DOCUMENTS

| ▨▨▨ Search Selected ▨▨▨ | ▨▨▨ Search ALL ▨▨▨ | Clear |

	PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
☐	4500933	February 1985	Chan	360/69
☐	4785469	November 1988	Joshi et al.	375/110
☐	5043938	August 1991	Ebersole	364/900
☐	5473264	December 1995	Mader et al.	326/30

☐	5481696	January 1996	Lomp et al.	395/500
☐	5548782	August 1996	Michael et al.	395/835
☐	5577213	November 1996	Avery et al.	395/280
☐	5612634	March 1997	MacKenna	326/62
☐	5644790	July 1997	Li et al.	395/883
☐	5754890	May 1998	Holmdahl et al.	
☐	5793999	August 1998	Mori	395/309
☐	5828905	October 1998	Rao	395/883
☐	5832244	November 1998	Jolley et al.	395/309
☐	5857112	January 1999	Hashemi et al.	395/828
☐	5928347	July 1999	Jones	710/129
☐	5935224	August 1999	Svancarek et al.	710/63
☐	6006295	December 1999	Jones et al.	710/62

FOREIGN PATENT DOCUMENTS

FOREIGN-PAT-NO	PUBN-DATE	COUNTRY	US-CL
0 860 781	February 1998	EP	
WO 97/31386	August 1997	WO	
WO 97/17214	April 1999	WO	

OTHER PUBLICATIONS

Universal Serial Bus Specification, Rev 1.1, Section 7.1.5: Device speed identification, pp. 113 and 114, Sep. 23, 1998.

ART-UNIT: 2825

PRIMARY-EXAMINER: Smith; Matthew

ASSISTANT-EXAMINER: Do; Thuan

ATTY-AGENT-FIRM: Kelly; Joseph R. Westman, Champlin & Kelly, P.A.

ABSTRACT:

A peripheral device is connectable to a computer having one of a first interface and a second interface. The first interface communicates with the peripheral device over a differential data connection having a first data conductor and a second data conductor. The second interface communicates with the peripheral device over a clock conductor and a single ended data connection which includes a data conductor. The peripheral device has first and second communication conductors configured for connection to the first and second data conductors in the differential data connection when the computer includes the first interface and is configured for connection to the first data conductor in the single ended data connection and the clock conductor when the computer is provided with the second interface. The peripheral device includes an interface detection component coupled to the first and second communication conductors and configured to detect which of the first and second interfaces the peripheral device is connected to. The peripheral device also includes a controller component configured to communicate between the peripheral device according to a protocol corresponding to the detected interface.

51 Claims, 9 Drawing figures